

## Data Sheet

## Industrial Rubbermate LED 2D

**18641**



<b>Designation:</b>	<b>18641 101 421</b>
Battery Requirement:	2x D
Bulb required:	3W CREE XP-E Q4 cool white LED
Luminous intensity:	High mode: 180 lm or 5330 cd Low mode: 80 lm
Range:	146m (calculated distance at maximum luminous intensity with an illuminance of 0.25 lux)
Weight:	264g (without batteries)
<b>Material:</b>	PC (Polycarbonate) ABS (Acrylonitrile Butadiene Styrene) TPR (Thermoplastic Rubber) Aluminum POM (Polyoxymethylene) All contact parts made of bronze or nickel plated steel
<b>Dimensions (mm):</b>	<b>A     210</b> <b>B     113.5</b> <b>C     68</b> <b>D     51.5</b>
<b>Run Time: High mode:</b>	<b>4 hours with VARTA HE</b>
<b>Low mode:</b>	<b>11 hours with VARTA HE</b>

### Features (Technical)

- Push switch (high/low/off)
- DC/DC regulator circuit
- Adjustable spot to flood beam
- Collimator lens provides long beam
- Rubber & aluminium grip handle
- Lighting leakage design when forget to turn off
- IPX4 Water resistant
- 5m Impact resistant