

## Examples of Environmental Product Declarations for Zumtobel Lighting Luminaires with typical characteristics

### VIVO L 27W LED830 TEC FL-S SRM

Ordering code: 60711878



LED spotlight with stabilized colour temperature "Essential Stable White", with TECTON adapter for simple and straightforward installation of luminaire on the TECTON continuous-row lighting system; 27 W LED/830

[Download EPD, datasheet etc.](#)

VIVO L 27W LED830

### PANOS INF E200HG 32W LED930 LDO WH

Ordering code: 60812666



Ceiling recessed "Stable White" LED luminaire, stabilized colour temperature; symmetric wide-beam light distribution with maximum luminaire efficiency and optimum photometric properties for office applications; 32 W LED/930

[Download EPD, datasheet etc.](#)

PANOS INF E200HG 32W LED930

### ECOOS ID 1/54W T16 LDE

Ordering code: 42177940



Indirect/direct luminaire with MPO micro-pyramidal optic, with digitally dimmable electronic ballast, DALI controllable luminaire for T16 lamp, 1/54 W. Direct light component guided via single-piece MPO-plus micro-pyramidal optic; ...

[Download EPD, datasheet etc.](#)

ECOOS ID 1/54W T16 LDE

**FEC2 B 3/14W T16 M625 LDE**

Ordering code: 42914936



Recessed DALI controllable luminaire for 3/14 W lamps, with reflector optic made of mat silver anodised pure aluminium, with digitally dimmable electronic ballast, ...

[Download EPD, datasheet etc.](#)  
FEC2 B 3/14W T16 M625 LDE

**TECTON 2/54W T16 LDE WH**

Ordering code: 42128552



Continuous-row luminaire 2 x 54 W T16, DALI controllable luminaire with digitally dimmable electronic ballast; ...

[Download EPD, datasheet etc.](#)  
TECTON 2/54W T16 LDE WH

**SCUBA PC 1/49W T16 EVG V2A**

Ordering code: 42174378



Moisture-proof diffuser luminaire 1/49W T16, with electronic ballast; fibreglass reinforced polyester housing, halogen-free, light grey; PC (polycarbonate) diffuser made as a single injection-moulded piece patterned with internal prisms; fitted to ceiling, wall or trunking using V2A standard spring clips; ...

[Download EPD, datasheet etc.](#)  
SCUBA PC 1/49W T16 EVG V2A

## RESCLITE C ESCAPE ED NSI WH

Ordering code: 42180396



LED Safety luminaire for escape-route illumination with a minimum output of 1 lx; ceiling recessed; Luminaire for central emergency lighting supply ... Luminaire total power: 5 W

[Download EPD, datasheet etc.](#)

RESCLITE C ESCAPE ED NSI WH

For more Environmental Product Declarations of Zumtobel Lighting Luminaires please have a look in our [online Product Data Base](#) (PDB) and look for precise product type or order number, section **downloads**.

If the EPD cannot be found directly, please contact your local Zumtobel Lighting representative.